





Features:

- Design Pressure (DP) / Maximum abnormal pressure (MAP) with the flow in the direction of the arrow on the body: 700 psig, 48 bar
- Design Pressure (DP) / Maximum abnormal pressure (MAP) with the flow against the direction of the arrow on the body: 350 psig, 24 bar
- Continuous operating temperature (COT): -40°F/300°F, -40°C/149°C
- Contact factory or visit website for compatibility with CFC, HCFC, HFC and HFO refrigerants and oils
- UL/cUL Listed, Conforms to Pressure Equipment Directive 2014/68/EU
- Forged brass body with full size openings for maximum flow and minimum pressure drop
- Diaphragms for positive isolation
- Thermally stable hand wheel for operation in wide temperature ranges



NPTFE to Flare



Solder to Solder

NPTFE to Flare

Part Number	NPTFE		Flare		A Open		B		C Min		Wt	
	in	mm	in	mm	in	mm	in	mm	in	mm	lb	kg
A 15525	1/4	6.35	1/4	6.35	2.82	72	1.30	33	1.04	26	0.71	0.32
A 15526	1/4	6.35	3/8	9.52	2.82	72	1.42	36	1.04	26	0.45	0.20
A 15530	1/2	12.7	1/2	12.7	3.70	94	1.86	47	1.44	37	1.17	0.53
A 15531	1/2	12.7	5/8	15.87	3.70	94	1.94	49	1.44	37	1.18	0.54

Solder to Solder

Part Number	OD		A Open		B		C		Wt	
	in	mm	in	mm	in	mm	in	mm	lb	kg
A 15539	1/4	6	2.85	72	1.11	28	0.76	19	0.69	0.31
A 15541	1/2	13	3.70	94	1.56	40	1.06	27	1.14	0.52
A 15542	5/8	17	3.70	94	1.44	37	0.94	24	1.14	0.52