

MUELLER REFRIGERATION COMPANY, Inc.

PRESSURE RELIEF VALVE SPECIFICATIONS

STANDARD, STANDARD WITH ACCESS, THREADED

PERFORMANCE:

**MAXIMUM WORKING PRESSURE /
BURST PRESSURE-**

**NOT APPLICABLE, SINCE VALVES HAVE VARIOUS
SET PRESSURES. VALVES ARE CERTIFIED TO
BUBBLE WITHIN +/- 3% OF THE SET PRESSURE AND
TO FULLY OPEN WITHIN -0% / + 10% OF THE SET
PRESSURE LISTED ON THE VALVE**

FLUID COMPATIBILITY-

**ALL TYPES OF FLUORINATED REFRIGERANTS
AND OILS**

RELIABILITY:

TEMPERATURE LIMITS-

-40°F / 300°F

LIFE EXPECTANCY-

**VALVES SHOULD BE REPLACED AFTER AN
INCIDENT HAS CAUSED THEM TO DISCHARGE TO
ENSURE NO FOREIGN MATERIALS HAVE IMPACTED
PERFORMANCE**

MATERIALS OF CONSTRUCTION

COMPLIANT WITH RoHS AND REACH DIRECTIVES

**BODY, BRASS -
SEAT HOLDER, BRASS -
SEAT -
SPRING, STEEL -
ADJUSTING SCREW, BRASS -
TAMER EVIDENT SEAL
(IF APPLICABLE), -**

**Brass
Brass
NEOPRENE WITH TEFLON COATING OR PTFE
STAINLESS STEEL
Brass

ALUMINUM**

CODE APPROVALS

**NATIONAL BOARD
ASME
CE
CRN
CSA**

**CERTIFIED SETTING AND DISCHARGE CAPACITIES
CERTIFIED MANUFACTURING PROCESS
CATEGORY IV (0086 – NOTIFIED BODY)
OGO314.9C
FILE#: 051529_0_00**