





Features:

- Design Pressure (DP) / Maximum abnormal pressure (MAP): 700 psig, 48 bar
- Continuous operating temperature (COT): -40°F/300°F, -40°C/149°C
- Contact factory or visit website for compatibility with CFC, HCFC, HFC and HFO refrigerants and oils
- UL/cUL Recognized, Conforms to Pressure Equipment Directive 2014/68/EU
- Forged brass body
- Corrosion resistant stem suitable for refrigerants and other industrial fluids
- Asbestos-free stem packing material



Flare to Flare



Solder to Solder

Flare to Flare

| Part Number | Size | A | | B | | C | | D | | Standard Cap | | Replacement Seal Cap | | Wt | |
|-------------|------|------|----|------|----|------|----|------|----|--------------|----------|----------------------|---------|---------|------|
| | | in | in | mm | in | mm | in | mm | in | mm | Material | Seal Cap | Brass | Plastic | lb |
| A 13591 | 1/4 | 3.48 | 88 | 1.00 | 25 | 0.94 | 24 | 1.44 | 37 | Brass | A 16474 | A 16474 | P 34627 | 0.43 | 0.20 |
| B 33482 | 1/4 | 3.40 | 86 | 1.00 | 25 | 0.94 | 24 | 1.40 | 36 | Brass | A 16474 | A 16474 | P 34627 | 0.51 | 0.23 |
| A 13595 | 3/8 | 3.40 | 86 | 1.12 | 28 | 0.94 | 24 | 1.40 | 36 | Brass | A 16474 | A 16474 | P 34627 | 0.48 | 0.22 |
| A 13592 | 1/2 | 3.40 | 86 | 1.25 | 32 | 0.94 | 24 | 1.44 | 37 | Brass | A 16474 | A 16474 | P 34627 | 0.50 | 0.22 |

Solder to Solder

| Part Number | Size | A | | B | | C | | D | | Standard Cap | | Replacement Seal Cap | | Wt | |
|--------------|------|------|----|------|----|------|----|------|----|--------------|----------|----------------------|---------|---------|------|
| | | in | in | mm | in | mm | in | mm | in | mm | Material | Seal Cap | Brass | Plastic | lb |
| A 15580 **** | 1/4 | 3.40 | 86 | 0.75 | 19 | 0.94 | 24 | 1.44 | 37 | Brass | A 16474 | A 16474 | P 34627 | 0.42 | 0.19 |
| A 15581 **** | 3/8 | 3.40 | 86 | 0.93 | 24 | 0.94 | 24 | 1.40 | 36 | Brass | A 16474 | A 16474 | P 34627 | 0.45 | 0.20 |
| A 15582 **** | 1/2 | 3.40 | 86 | 0.87 | 22 | 0.94 | 24 | 1.40 | 36 | Brass | A 16474 | A 16474 | P 34627 | 0.54 | 0.25 |

Brass cap Includes copper gasket

**** Pack gland, packing and pack washer packaged separately in bag. Stem and seal cap loosely assembled in valve.